

## WAGNER Classic SAE 10W/40 Premium

---

Semi-synthetic high-performance engine oil of the latest generation for petrol and diesel engines.

### Applications

---

Suitable for vintage and classic cars with and without turbo charger.

This engine oil also can be used in motorcycle engines with multiple disc clutches in oil bath (wet clutch/oil bath clutch) and as year-round oil for the mixed fleet.

### Specifications

- API SN/CI-4

### How It Works

---

The selected base oils and additives do not damage white metals, non-ferrous alloys and sealing materials of classic cars.

WAGNER Classic Engine Oil SAE 10W/40 Premium is based on the high-quality Engine Oil Additive SAE 30 Classic. Besides the standard blending typical for engine oils, this high-performance oil is able to smooth metal surfaces.

Wear and friction resistance are reduced, which is why engine performance is improved and fuel is saved. Due to smoothed surfaces, there is less running noise in the motor and an outstanding emergency lubrication is supplied, if necessary.

The use of this high-quality engine oil offers maximum protection against sludge, coking and varnish formation of the engine interior and guarantees a clean, residue-free motor.

### Advantages

---

- excellent cleaning power
- highest security against sludge, coking and varnish formation of the engine interior
- clean, residue-free engine
- unique smoothing effect of the metals
- reduction of mechanical noise in the engine
- excellent emergency lubrication

## WAGNER Classic SAE 10W/40 Premium

### Technical Data WAGNER Classic SAE 10W/40 Premium

Property	Test method	Test result	Unit
Boiling point/boiling range		≥ 370	°C
Flash point	DIN ISO 2592	≥ 310	°C
Ignition temperature	ASTM E 659	≥ 250	°C
Lower explosion limit	in case of formation of oil sprays	ca. 0.6	Vol%
Upper explosion limit	in case of formation of oil sprays	ca. 6.5	Vol%
Vapour pressure (@i 370 °C)		1013	mbar
Relative density	DIN 51562	861-871	kg/m <sup>3</sup>
Solubility in water		Insoluble	
Vapour pressure (air = 1)		vapours, heavier than air	
Viscosity @ 40 °C	DIN 51562	80-110	mm <sup>2</sup> /s

### Packaging

Available Container	Content	Item No.
Metal canister with handle	5 l	022005
Plastic canister	20 l	022020
Tight head drum (steel sheet)	200 l	022200

The information of this datasheet is made to the best of our knowledge and advises only a technically certified user on possible applications. WAGNER Spezialschmierstoffe is not liable for any property damage incurred as a result of improper use, mishandling, and or any use outside the prescribed method of use, purpose, or application. Any and all warranty and or damage claims will be subject to investigation on the use, method of application, and intent of application of the used product.