

## WAGNER Classic Engine Oil SAE 20 unalloyed

Unalloyed multi-grade motor oil made from special, carefully selected raffinates.

### Scope of Application:

WAGNER Classic Engine Oil SAE 20 unalloyed can be used in:

- classic cars, motorcycle and utility vehicles without full-flow oil filter, because it does not contain any cleaning and dirt removal additives (DD-detergent-dispersing additives).
- motorcycle engines with multi-disc clutch in oil bath (wet clutch / oil bath clutch)

### Tried and tested in applications requiring adherence to manufacture's fluid specifications

- API SA

### Advantages:

- resistant to oxidation
- not foaming
- excellent viscosity - temperature behaviour
- perfect lubrication at low and high temperatures
- does not damage white metal, non-ferrous metal alloys and sealing materials of classic vehicles

### Technical Data:

WAGNER SAE 20 unalloyed	Test Method	Test Result	Unit
Form		liquid	
Colour		yellow, brown	
Boiling point / Boiling range		≥ 320	°C
Flash point	DIN ISO 2592	≥ 220	°C
Ignition temperature	ASTEM E 659	≥ 250	
Explosion limits lower	in case of formation of oil sprays	ca. 0.6	Vol%
Lower upper		ca. 6.5	Vol%
Vapour pressure (@i 320 °C)		1,013	mbar
Relative density	DIN 515625	875-892	kg/m <sup>3</sup>
Solubility in water		insoluble	
Vapour pressure (air= 1)		vapours, heavier than air	
Viscosity (@ 40°C)	DIN 51562	5-200	mm <sup>2</sup> /s

Content:	Item no.:	Unit:
1 l	420001	10 x 1 l
5 l	420005	4 x 5 l
20 l	420020	
200 l	420200	

The information of this datasheet is made to the best of our knowledge and advises only a technically certified user on possible applications. WAGNER Spezialschmierstoffe is not liable for any property damage incurred as a result of improper use, mishandling, and or any use outside the prescribed method of use, purpose, or application. Any and all warranty and or damage claims will be subject to investigation on the use, method of application, and intent of application of the used product.

### Wagner Spezialschmierstoffe GmbH & Co. KG

Speckbrodi 8 - 86759 Wechingen, Germany - Tel +49 9085 960 110 - Fax +49 9085 960 900

[wagner@wagner-german-oil.com](mailto:wagner@wagner-german-oil.com) - [www.wagner-german-oil.com](http://www.wagner-german-oil.com)