

WAGNER Classic Engine Oil SAE 20 unalloyed

Unalloyed multi-grade motor oil made from special, carefully selected raffinates.

Applications

WAGNER Classic Engine Oil SAE 20 unalloyed can be used in:

- classic cars, motorcycle and utility vehicles without full-flow oil filter, because it does not contain any cleaning and dirt removal additives (DD-detergent-dispersing additives).
- motorcycle engines with multi-disc clutch in oil bath (wet clutch / oil bath clutch)

Specifications

- API SA

Advantages

- resistant to oxidation
- not foaming
- excellent viscosity - temperature behaviour
- perfect lubrication at low and high temperatures
- does not damage white metal, non-ferrous metal alloys and sealing materials of classic vehicles

Technical Data WAGNER Classic SAE 20 unalloyed

Property	Test method	Test result	Unit
Density @ 15 °C	DIN EN ISO 12185	0.864	g/cm ³
Viscosity kinematic @ 40 °C	DIN 51562-1	44.8	mm ² /s
Viscosity kinematic @ 100 °C	DIN 51562-1	6.8	mm ² /s
Viscosity index	DIN ISO 2909	113	
Flash point COC	DIN ISO 2592	230	°C
Pour point	DIN ISO 3016	-24	°C
FZG-test A8,3/90	DIN ISO 14635-1		SKS:13

Packaging

Available Container	Content	Item No.
Metal canister	1 l	420001
Metal canister with handle	5 l	420005
Plastic canister	20 l	420020
Tight head drum (steel sheet)	200 l	420200

The information of this datasheet is made to the best of our knowledge and advises only a technically certified user on possible applications. WAGNER Spezialschmierstoffe is not liable for any property damage incurred as a result of improper use, mishandling, and or any use outside the prescribed method of use, purpose, or application. Any and all warranty and or damage claims will be subject to investigation on the use, method of application, and intent of application of the used product.