

## WAGNER Chain Adhesive Spray

**Fully synthetic chain spray for lubricating all types of chains.**

### Applications

The product is ideally suited for e.g. toothed wheels and chains on motorcycles, mopeds, mopeds, mopeds, bicycles, forklifts and construction machinery.

Due to the wide temperature range of - 30 ° C to + 250 °C, it is also suitable for drive and transport chains in drying ovens, pasteurizers, painting and baking ovens, wire ropes and much more.

### Advantages

- all-round lubricant
- good adhesion and creep ability
- very suitable for O-ring chains
- high centrifugal forces
- no dripping
- high temperatures, high tensile forces
- O-ring neutral
- nontoxic
- adhesive
- does not attract dust
- water-resistant

### Technical Data WAGNER Chain Adhesive Spray

Property	Test method	Test result	Unit
Colour		transparent	
Viscosity class	ISO-VG	220	
Base		Ester	
Density 20 °C		970	kg/m <sup>3</sup>
Temperature range		-30 - > 250	°C
Viscosity 40 °C		220	mm <sup>2</sup> /s
Viscosity 100 °C		25	mm <sup>2</sup> /s
Flash point COC		280	°C
Viscosity index		150	
Pour point		- 27	°C

### Packaging

Available Container	Content	Item No.
Spray can	400 ml	162400

The information of this datasheet is made to the best of our knowledge and advises only a technically certified user on possible applications. WAGNER Spezialschmierstoffe is not liable for any property damage incurred as a result of improper use, mishandling, and or any use outside the prescribed method of use, purpose, or application. Any and all warranty and or damage claims will be subject to investigation on the use, method of application, and intent of application of the used product.