

WAGNER Motorcycle Engine Oil Classic 4 T SAE 20W/50

WAGNER
High Quality Lubricants

High-performance motor oil based on mineral oil.

Applications

A specially developed and balanced additive technology for demanding air- and water-cooled 4-stroke motorcycle engines with wet or oil-lubricated clutches guarantees excellent lubricating film adhesion and excellent friction.

Recommendation

- JASO MA2 / MA
- API SL/SJ/SG

Advantages

- very good high temperature stability
- high wear protection
- ideal lubrication safety even at highest temperatures and speeds
- protection against deposits on pistons and valves
- significant reduction of black sludge
- decreasing oil consumption
- prevention of clutch slippage or sticking in all phases of operation

Technical Data WAGNER Motorcycle Engine Oil Classic 4 T SAE 20W/50

Property	Test method	Test result	Unit
Density (@ 15 °C)	DIN EN ISO 12185	0.860 – 0.900	g/cm ³
Kin. viscosity (@ 100 °C)	ASTM D7279	17.5 – 18.9	mm ² /s
Viscosity index (VI)	ASTM D2270	min. 121	
Total Base Number	ASTM D2896	5.8 – 7.2	mg KOH/g
Dyn. viscosity (@ -15 °C)	ASTM D5293	max. 9,500	mPa*s
Flash point COC	DIN ISO 2592	min. 200	°C
Pourpoint	ASTM D7346	max. -30	°C

Packaging

Available Container	Content	Item No.
Plastic canister	1 l	110001
Plastic canister	5 l	110005
Plastic canister	20 l	110020
Tight head drum (steel sheet)	200 l	110200

The information of this datasheet is made to the best of our knowledge and advises only a technically certified user on possible applications. WAGNER Spezialschmierstoffe is not liable for any property damage incurred as a result of improper use, mishandling, and or any use outside the prescribed method of use, purpose, or application. Any and all warranty and or damage claims will be subject to investigation on the use, method of application, and intent of application of the used product.