

WAGNER Fluid Grease for Gears

Very soft and smooth special product for gear lubrication of vintage motorcycles, classic cars and commercial vehicles.

Application

WAGNER Fluid Grease for Gears was specially adapted to old moped and motorcycle gearboxes.

It has been tested a hundred times in transmissions of DKW and Sachs motors with wet clutch. Not necessary to mix it with oil, as recommended formerly for Shell Ambrolem or Retinax G. WAGNER Fluid Grease for Gears can be filled undiluted and retains its smooth consistency even at lower temperatures.

Due to the low viscosity, the so-called mixing with unalloyed oils, which is often required in the operating instructions, is not necessary.

- lubrication of manual transmissions of vintage motorcycles according to manufacturer's instructions, differentials and steering gears of classic cars and commercial vehicles
- angular gears in construction and agricultural machinery
- central lubrication systems of commercial vehicles, especially for very narrow and long lubrication lines

Advantages

- wide service temperature range from -50 to + 120 ° C
- high oxidation and water resistance
- good corrosion protection
- increased pressure absorption capacity by additives that improve lubrication and reduce wear
- good adhesion

Technical data

WAGNER Fluid Grease for Gears	Test method	Test result	Unit
Consistency class NLGI		00/000	
Temperature range		-50 - +120	°C
Wear Protection VKA welding load		2200	N
Dropping point	DIN ISO 2176	170	°C
Worked penetration	DIN ISO 2137	400 – 460	1/10 mm
Water resistance	DIN 51 807 T1	1 – 90	
Thickener		Lithium	
Base oil viscosity (40 °C)	DIN 51 562	45	mm ² /s
Flow pressure (- 35 °C)	DIN 51 805	40	mbar

Content	Item no.	Unit
250 ml	154250	
900 g	154900	20 x 900 g

The information of this datasheet is made to the best of our knowledge and advises only a technically certified user on possible applications. WAGNER Spezialschmierstoffe is not liable for any property damage incurred as a result of improper use, mishandling, and or any use outside the prescribed method of use, purpose, or application. Any and all warranty and or damage claims will be subject to investigation on the use, method of application, and intent of application of the used product.

Wagner Spezialschmierstoffe GmbH & Co. KG

Speckbrodi 8 - 86759 Wechingen, Germany - Tel +49 (0)9085 960 110 - Fax +49 (0)9085 960 900

wagner@wagner-german-oil.com - www.wagner-german-oil.com