

## WAGNER Classic HD SAE 30

High-alloyed, mineral HD single grade engine oil of the highest class.

Indispensable for classic cars, motorbikes and commercial vehicles – special lubricant that matches perfectly with their technical requirements.

The clearly defined viscosity index offers high safety reserves in case of boundary lubrication conditions and stable oil pressure. Due to its high additive content, it offers excellent detergent, dispersant and anti-wear properties and protects from corrosion and black sludge formation.

### Scope of Application:

WAGNER Classic HD SAE 30 is very well suited for use in mixed car pool, for petrol and diesel engines with and without turbocharging in passenger cars.

For classic cars with oil filters, commercial vehicles, motorcycles and stationary systems. WAGNER Classic HD SAE 30 can also be used for lubrication of 2-stroke diesel engines.

### Tried and tested in applications requiring adherence to manufacture's fluid specifications

- API CE/SG
- API CF4
- MIL-L46 152 E
- MIL-L-2104 D und E
- Allison C-4
- MB-Blatt 228.0
- MAN 270
- VW 501 00 und 505 00
- ZF TE-ML 02, 03, 04, 06, 10 und 14
- CCMC (ACEA) D4, G4

Its base oils and additives used are selected so that white metals, non-ferrous metal alloys and sealing materials used in classic cars are not damaged. This engine oil can be used in motorcycle engines with multi-disc clutch in oil bath (wet clutch / oil bath clutch) and can be mixed with every HD engine oil based on mineral oil.

### Advantages:

- high safety reserve in case of boundary lubrication
- stable oil pressure
- strong wear and corrosion protection
- avoids black sludge formation

### Technical Data:

WAGNER Classic HD SAE 30	Test Method	Test Result	Unit
Density (15 °C)	DIN EN ISO 12185	873	kg/m <sup>3</sup>
Flash point COC	DIN ISO 2592	> 220	°C
Pour point	DIN ISO 3016	- 33	°C
Viscosity (40 °C)	DIN 51562-1	78.2	mm <sup>2</sup> /s
Viscosity (100 °C)	DIN 51562-1	10.2	mm <sup>2</sup> /s
VI	DIN ISO 2909	113	

### Wagner Spezialschmierstoffe GmbH & Co. KG

Speckbrodi 8 - 86759 Wechingen, Germany - Tel +49 9085 960 110 - Fax +49 9085 960 900

[wagner@wagner-german-oil.com](mailto:wagner@wagner-german-oil.com) - [www.wagner-german-oil.com](http://www.wagner-german-oil.com)

**WAGNER Classic HD SAE 30**

---

<b>Content:</b>	<b>Item no.:</b>	<b>Unit:</b>
1 l	330001	10 x 1 l
5 l	330005	4 x 5 l
20 l	330020	
200 l	330200	

The information of this datasheet is made to the best of our knowledge and advises only a technically certified user on possible applications. WAGNER Spezialschmierstoffe is not liable for any property damage incurred as a result of improper use, mishandling, and or any use outside the prescribed method of use, purpose, or application. Any and all warranty and or damage claims will be subject to investigation on the use, method of application, and intent of application of the used product.

---

**Wagner Spezialschmierstoffe GmbH & Co. KG**

Speckbrodi 8 - 86759 Wechingen, Germany - Tel +49 9085 960 110 - Fax +49 9085 960 900

[wagner@wagner-german-oil.com](mailto:wagner@wagner-german-oil.com) - [www.wagner-german-oil.com](http://www.wagner-german-oil.com)