

WAGNER 2-Stroke Power Mix

Fuel additive made of wear protection additives, combustion activating agents, cleaning and anticorrosion agents for optimizing engine performance and cleanliness of two-stroke engines.

Application

2-Stroke Power-Mix can be used as fuel additive in all two-stroke gasoline engines, such as:

- scooters, mopeds (vintage, classic, new vehicles)
- small engines (chainsaws, lawn mowers, model engines)
- outboard motors

How It Works

Friction-reducing additives reduce the internal friction of the motors and thus protect against deposits.

Catalytic agents provoke a significantly more efficient combustion which results in an increase in performance, an improvement in torque and a higher end speed.

Advantages

- wear reduction
- improvement in torque and end speed
- increase in performance
- reduction of fuel consumption
- safe full-load operation
- less deposits
- deoiled exhaust system
- corrosion protection when unused for a longer time
- clean combustion and less oiling
- extended engine service life

Technical Data

WAGNER 2-Stroke Power-Mix	Test method	Test result	Unit
pH-value, undiluted		7.5	
Density		0.92	g/ml
Viscosity (20 °C)		12.5	mm/s ²
Flash point	(in closed cup)	> 85	°C

Dosing

Before refueling, add WAGNER 2-Stroke Power-Mix in a mixing ratio of 1: 200.
100 ml of WAGNER 2-Stroke Power-Mix are sufficient for 20 litres of gasoline/petrol.

Not suitable for admixture in nitromethane fuels.

Please note!

Avoid overdosing. When overdosing, the combustion chamber temperature increases considerably. Furthermore, WAGNER 2-Stroke Power-Mix does not replace the two-stroke oil to be added to the fuel.

Wagner Spezialschmierstoffe GmbH & Co. KG

Speckbrodi 8 - 86759 Wechingen, Germany - Tel +49 9085 960 110 - Fax +49 9085 960 900
wagner@wagner-german-oil.com - www.wagner-german-oil.com

WAGNER 2-Stroke Power Mix

Content	Item no.	Unit
100 ml	046100	35 x 100 ml
1 l	047001	10 x 1 l
5 l	047005	4 x 5 l

The information of this datasheet is made to the best of our knowledge and advises only a technically certified user on possible applications. WAGNER Spezialschmierstoffe is not liable for any property damage incurred as a result of improper use, mishandling, and or any use outside the prescribed method of use, purpose, or application. Any and all warranty and or damage claims will be subject to investigation on the use, method of application, and intent of application of the used product.

Wagner Spezialschmierstoffe GmbH & Co. KG

Speckbrodi 8 - 86759 Wechingen, Germany - Tel +49 9085 960 110 - Fax +49 9085 960 900

wagner@wagner-german-oil.com - www.wagner-german-oil.com