

WAGNER Motorcycle Engine Oil Premium 4 T

SAE 10W/40

WAGNER
High Quality Lubricants

High-performance motor oil based on HC synthetic oil.

Applications

A specially developed and balanced additive technology for demanding air- and water-cooled 4-stroke motorcycle engines with wet or oil-lubricated clutches guarantees excellent lubricating film adhesion and excellent friction.

Recommendation

- JASO MA2 / MA
- API SL/SJ/SG

Advantages

- very good high temperature stability
- high wear protection
- ideal lubrication safety even at highest temperatures and speeds
- protection against deposits on pistons and valves
- significant reduction of black sludge
- decreasing oil consumption
- prevention of clutch slippage or sticking in all phases of operation

Technical Data WAGNER

Property	Test method	Test result	Unit
Density (@ 15 °C)	EN ISO 12185	0.830 – 0.870	g/cm ³
Kin. viscosity (@ 100 °C)	DIN 51562-1	13.8-15.2	mm ² /s
Viscosity index (VI)	DIN ISO 2909	min. 155	
Dyn. viscosity (@ -25 °C)	DIN 51377	max. 7,000	mPa s
Total Base Number	DIN ISO 3771	5,4-7.0	mg KOH/g
Pourpoint	DIN ISO 3016	max. -39	°C
Flash point COC	DIN ISO 2592	min. 200	°C

Packaging

Available Container	Content	Item No.
Plastic canister	1 l	111001
Plastic canister	5 l	111005
Plastic canister	20 l	111020
Tight head drum (steel sheet)	200 l	111200

The information of this datasheet is made to the best of our knowledge and advises only a technically certified user on possible applications. WAGNER Spezialschmierstoffe is not liable for any property damage incurred as a result of improper use, mishandling, and or any use outside the prescribed method of use, purpose, or application. Any and all warranty and or damage claims will be subject to investigation on the use, method of application, and intent of application of the used product.